


- output shaft bearing: grooved ball bearing 2RS
- max. radial load: 1300N by n2=100 1/min Lh > 10.000h
 - max. axial load: 500N by n2=100 1/min Lh > 10.000h
 - reference to shaft center at temp. = 30°C
- straight-toothed planetary gearbox
- backlash at output shaft:
- ≤ 10 arcmin; reduced ≤ 6 arcmin

- lifetime: > 30.000h
- efficiency: by rated load 94% (depends on ratio)
- lubrication: lifetime-lubrication
- nominal output torque at n1 = 3000 1/min
- operating temperature: -20°C bis +90°C
- motor mounting: M2 (stocked driving pinion)
- torque of clamping screw: 6 Nm
- operation mode: S1
- operation ratio: CB1
- protection system IP 54

i =	3	4	5	7	10
nominal output torque [Nm]	40	54	54	54	40
max. acceleration torque [Nm]	70	100	100	100	75
emergency torque [Nm]	160	216	216	216	160

Zust.	Änderung	Datum	Name	Ursprung:	Ersatz für:	Ersatz durch:
Verwendungsbereich				Allgemein-toleranzen ISO 2768-mH	Kanten ISO 13715	Maßstab (Werkstoff, Halbzeug) (Rohteil-Nr) (Modell- oder Gesenk-Nr)
				Datum	Name	EPL 84/1 19x40
				Bearb. 25.06.16	BITZER	
				Gepr. Norm		
				Tolerierung ISO 8015		pd80 bc100 4xø7 ø120
						DS0840405-1
						Blatt 1
						1 Bl.

consider mounting instruction
subject to modifications