



output shaft bearing: grooved ball bearing 2RS

- max. radial load: 1300N by n2=100 1/min Lh > 10.000h
- max. axial load: 500N by n2=100 1/min Lh > 10.000h
- reference to shaft center at temp. = 30°C

straight-toothed planetary gearbox
backlash at output shaft:

≤ 14 arcmin; reduced ≤ 8 arcmin

lifetime: > 30.000h

efficiency: by rated load 92% (depends on ratio)

lubrication: lifetime-lubrication

nominal output torque at n1 = 3000 1/min

operating temperature: -20°C bis +90°C

motor mounting: M2 (stocked driving pinion)

- torque of clamping screw: 6 Nm
- operation mode: S1
operation ratio: CB1
protection system IP 54

	i =	12	16	20	25	35	40	50	70	100
	nominal output torque [Nm]	80	100	100	100	100	100	100	100	64
	max. acceleration torque [Nm]	100	125	125	125	125	125	125	125	80
	emergency torque [Nm]	160	216	216	216	216	216	216	216	160

consider mounting instruction
subject to modifications

Zust	Änderung	Datum	Name	Ursprung	Eiselle Antriebstechnik		Ersatz für:	Ersatz durch:	Blatt
					Allgemein- toleranzen ISO 2768-mH	Kanten ISO 13715	Maßstab (Werkstoff, Halbzeug) (Rohteil-Nr) (Modell- oder Gesenk-Nr)		1
					Bearb. 25.06.16	BITZER	EPL 84/2 19x40		1
					Norm		pd70 bc90 4xM5 sq90		
					Tolerierung ISO 8015		DS0840461-2		