



- output shaft bearing: grooved ball bearing 2RS
- max. radial load: 2600N by $n_2=100$ 1/min $L_h > 10.000h$
 - max. axial load: 1000N by $n_2=100$ 1/min $L_h > 10.000h$
 - reference to shaft center at temp. = 30°C
- straight-toothed planetary gearbox
- backlash at output shaft:
- ≤ 8 arcmin; reduced ≤ 6 arcmin

lifetime: > 30.000h

efficiency: by rated load 94% (depends on ratio)

lubrication: lifetime-lubrication

nominal output torque at $n_1 = 3000$ 1/min

operating temperature: -20°C bis +90°C

motor mounting: M2 (stocked driving pinion)

- torque of clamping screw: 20 Nm
- operation mode: S1
- operation ratio: CB1
- protection system IP 54

	$i =$	3	4	5	7	10
nominal output torque [Nm]		100	120	120	120	105
max. acceleration torque [Nm]		180	200	200	200	180
emergency torque [Nm]		200	480	480	480	410

consider mounting instruction
subject to modifications

Zust.	Änderung	Datum	Name	Ursprung:	Ersatz für:	Ersatz durch:	Blatt
							1
Verwendungsbereich				Allgemein-toleranzen ISO 2768-mH	Kanten ISO 13715	Maßstab (Werkstoff, Halbzeug) (Rohteil-Nr) (Modell- oder Gesenk-Nr)	(Gewicht)
Datum				Bearb. 08.08.16	Name BITZER	EPL 118/1 19x40	
Norm				Gepr.		pd110 bc130 4x$\varnothing 9$ $\varnothing 160$	
Tolerierung ISO 8015						DS1180428-1	
						Blatt 1	
						1 Bl.	

