



output shaft bearing: grooved ball bearing 2RS

- max. radial load: 2600N by $n_2=100$ 1/min $L_h > 10.000h$
- max. axial load: 1000N by $n_2=100$ 1/min $L_h > 10.000h$
- reference to shaft center at temp. = 30°C

straight-toothed planetary gearbox
backlash at output shaft:

≤ 12 arcmin; reduced ≤ 8 arcmin

lifetime: $> 30.000h$

efficiency: by rated load 92% (depends on ratio)

lubrication: lifetime-lubrication

nominal output torque at $n_1 = 3000$ 1/min

operating temperature: -20°C bis +90°C

motor mounting: M2 (stocked driving pinion)

- torque of clamping screw: 20 Nm
- operation mode: S1
- operation ratio: CB1
- protection system IP 54

	i =											
nominal output torque [Nm]	12	16	20	25	35	40	50	70	100			
max. acceleration torque [Nm]	170	210	210	210	210	210	210	210	165			
emergency torque [Nm]	215	255	255	255	255	255	255	255	180			
	400	480	480	480	480	480	480	480	410			

consider mounting instruction
subject to modifications

Zust.	Änderung	Datum	Name	Ursprung:	Maßstab	(Gewicht)
				Allgemein- toleranzen ISO 2768-mH	ISO 13715	(Werkstoff, Halbzeug) (Rohteil-Nr.) (Modell- oder Gesenk-Nr.)
				Bearb. 04.10.16 Gepr. Norm	Datum Name BITZER	EP L 118/2 19x40
				Tolerierung ISO 8015		pd/0 bc-90 4xø7 ø118
						DS1180443-2
						Blatt 1
						1 Bl.

