



output shaft bearing: grooved ball bearing 2RS

- max. radial load: 2600N by  $n_2=100$  1/min  $L_h > 10.000h$
- max. axial load: 1000N by  $n_2=100$  1/min  $L_h > 10.000h$
- reference to shaft center at temp. = 30°C

straight-toothed planetary gearbox

backlash at output shaft:

≤ 8 arcmin; reduced ≤ 6 arcmin

lifetime: > 30.000h

efficiency: by rated load 94% (depends on ratio)

lubrication: lifetime-lubrication

nominal output torque at  $n_1 = 3000$  1/min

operating temperature: -20°C bis +90°C

motor mounting: M2 (stocked driving pinion)

- torque of clamping screw: 20 Nm
- operation mode: S1
- operation ratio: CB1
- protection system IP 54

	i =	3	4	5	7	10
nominal output torque [Nm]		100	120	120	120	105
max. acceleration torque [Nm]		180	200	200	200	180
emergency torque [Nm]		200	480	480	480	410

Verwendungsbereich		Allgemein-toleranzen ISO 2768-mH	Kanten ISO 13715	Maßstab (Werkstoff, Halbzeug) (Rohteil-Nr) (Modell- oder Gesenk-Nr)	(Gewicht)	
Datum		Bearb. 26.09.16	Name BITZER	EPL 118/1 24x50		
Norm		Gepr.		pd130 bc165 4xM10 sq14.0		
Tolerierung ISO 8015						
Zust.	Änderung	Datum	Name	Ursprung:	Ersatz für:	Ersatz durch:
				<b>Eiselle</b> Antriebs-technik	DS1180412-1	
consider mounting instruction subject to modifications						
Blatt 1						
1 Bl.						