



output shaft bearing: grooved ball bearing 2RS

- max. radial load: 2600N by n2=100 1/min Lh > 10.000h
- max. axial load: 1000N by n2=100 1/min Lh > 10.000h
- reference to shaft center at temp. = 30°C

straight-toothed planetary gearbox
backlash at output shaft:

≤ 8 arcmin; reduced ≤ 6 arcmin

lifetime: > 30.000h

efficiency: by rated load 94% (depends on ratio)

lubrication: lifetime-lubrication

nominal output torque at n1 = 3000 1/min

operating temperature: -20°C bis +90°C

motor mounting: M2 (stocked driving pinion)

- torque of clamping screw: 20 Nm
- operation mode: S1
operation ratio: CB1
protection system IP 54

i =	3	4	5	7	10
nominal output torque [Nm]	100	120	120	120	105
max. acceleration torque [Nm]	180	200	200	200	180
emergency torque [Nm]	200	480	480	480	410

consider mounting instruction
subject to modifications

Zust.	Änderung	Datum	Name	Ursprung:	Ersatz für:	Ersatz durch:	Blatt 1
					DS1180422-1		1 Bl.
Verwendungsbereich				Allgemein- toleranzen ISO 2768-mH	Kanten ISO 13715	Maßstab (Werkstoff, Halbzeug) (Rohteil-Nr.) (Modell- oder Gesenk-Nr.)	(Gewicht)
			Datum	Name			
			Bearb. 26.09.16	BITZER		EP L 118/1 24x50	
			Gepr.			pd110 bc130 4xM8 sq120	
			Norm				
			Tolerierung ISO 8015				
				Eiselle ANTRIEBSTECHNIK			