



output shaft bearing: taper roller bearing

- max. radial load: 6300N by $n_2=100$ 1/min Lh > 10.000h
- max. axial load: 5600N by $n_2=100$ 1/min Lh > 10.000h
- reference to shaft center at temp. = 30°C

straight-toothed planetary gearbox

backlash: $\leq 3 / 5$ arcmin reference to output shaft

torsional stiffness: 40 Nm/arcmin

lifetime: > 30.000h

efficiency at load: 96% (depends on ratio)

lubrication: lifetime lubrication

running noise: ≤ 64 dbA (measured in 1m distance at $n_1=3000$ 1/min)

nominal output torque at $n_1 = 3000$ 1/min

$i =$	3	4 / 5 / 7	10
nominal output torque [Nm]	110	150	115
max. acceleration torque [Nm]	180	250	200
emergency torque [Nm]	500	600	500

allowed average speed: 4000 1/min

- max. speed: 6000 1/min (allowed operating temp. must be considered)
- operating temperature: -20°C bis +90°C
- motor mounting: M2 (supported drive pinion)
- torque of clamping screw: 35 Nm

operation mode: S1

operation ratio: CB1

protection system IP 65

consider mounting instruction
subject to modifications

Zust	Anderung	Datum	Name	Ursprung:		
					Ersatz für:	
					Ersatz durch:	
Verwendungsbereich			Allgemein- toleranzen ISO 2768-mH		Kanten ISO 13715	
Datum			Bearb. 07.08.16		Name BITZER	
Norm			Gepr.			
Tolerierung ISO 8015			Tolerierung ISO 8015			
Eisela Antriebs-technik					Maßstab (Werkstoff Halbzeug) (Rohteil-Nr) (Modell- oder Gassenk-Nr)	
ESP 100/1 32x60					pd180 bc215 4xM12 sq190	
DS1000416-1					Blatt 1	
					1 Bl.	