



output shaft bearing: grooved ball bearing 2RS

- max. radial load: 6500N by n2=100 1/min Lh > 10.000h
 - max. axial load: 6000N by n2=100 1/min Lh > 10.000h
 - reference to shaft center at temp. = 30°C
- straight-toothed planetary gearbox
backlash at output shaft:

≤ 8 arcmin; reduced ≤ 6 arcmin
lifetime: > 30.000h
efficiency: by rated load 94% (depends on ratio)

- lubrication: lifetime-lubrication
- nominal output torque at n1 = 3000 1/min
operating temperature: -20°C bis +90°C
motor mounting: M2 (stocked driving pinion)
- torque of clamping screw: 20/35 Nm
- operation mode: S1
operation ratio: CB1
protection system IP 54

i =	3	4	5	7	10
nominal output torque [Nm]	230	310	310	310	180
max. acceleration torque [Nm]	360	460	460	460	340
emergency torque [Nm]	860	1000	1000	1000	800

consider mounting instruction
subject to modifications

Zust	Anderung	Datum	Name	Ursprung:	Ersatz für:	Ersatz durch:	Blatt 1
					DS1500407-1		1 Bl.
Verwendungsbereich				Allgemein- toleranzen ISO 2768-mH	Kanten ISO 13715	Maßstab (Werkstoff, Halbzeug) (Rohteil-Nr) (Modell- oder Gesenk-Nr)	(Gewicht)
Datum				Bearb. 25.03.17	Name BITZER	EPL 150/1 24x50	
Norm				Gepr.		pd80 bc100 4xM6 sq140	
Tolerierung ISO 8015							
EISENIE Antriebs-technik							